

Tyde 2 Home Desk

Ronan & Erwan Bouroullec, 2024

Table tops

Substrate for HPL, melamine and veneer table tops

Description: high-density three-ply fine particle board panels for interior fittings (including furniture), for use in dry conditions) in accordance with DIN EN 312.

Table top thickness: approx. 22 mm.

Safety: all corners and edges are rounded. Emission levels are below the legal limit specified for emission class E1 (non-hazardous).

Melamine-faced table tops

Description: the laminated chipboard (MFB = melamine-faced board) is a fine particle board (P2) coated with melamine resin in accordance with DIN EN 14322.

Surface: reflection values, sheen and brightness are below the thresholds recommended for standard workstations.

Edge: the table top has ABS lipping, 3 mm thick.

Safety: all corners and edges are rounded.

HPL table tops with anti-fingerprint coating

Description: laminate (HPL = high-pressure laminate) in accordance with DIN EN 438-2, glued to both sides of the above-mentioned substrate.

Surface: the reflection values, sheen and brightness levels of the black surface do not comply with the guidelines recommended for computer workstations; therefore, this product version does not bear the GS Seal.

Edge: the table top has ABS lipping (2 mm thick).

Safety: all corners and edges are rounded.

Genuine wood veneer table tops

Description: light oak veneer with continuous grain pattern.

Surface: protected by multiple coats of polyurethane lacquer.

Edge: continuous flat wood veneer lipping, 2.5–3 mm thick.

Safety: all corners and edges are rounded.

The maximum load capacity per seat is 100 kg.

Under-table elements

Leg columns

Description: precision columns made of tubular steel, powder-coated, diameter 70 mm. For motor-driven height-adjustable columns, the electrical control system is integrated in the master column, while the follower column is controlled via motor cable. The columns are attached directly to the die-cast side element and the frame tubes.

Height-adjustment: telescoping 3-tier column, continuous height adjustment from 650 to 1250 mm, motor-operated. Motors are integrated in the column. Fixed height is 74 cm.

Glides with levelling adjustment (+/- 5 mm) for uneven floors.

Safety: anti-collision device with desk sensor to protect against material damage; plug-in adapter using gyro-based technology detects any slope in the angle of the table top and triggers an immediate stop and change in direction of movement to avoid material damage. Anti-collision sensors are a technical safety feature of the table system; they are not designed to protect against personal injury or pinching. Deliberate and controlled height adjustment of the table on the part of the user remains absolutely essential.

Control unit

The control unit is equipped with a memory function, display and key lock. Before the lever switch can be activated to adjust the table height, the control unit must first be unlocked with a predefined key combination.

Tyde 2 Home Desk

Ronan & Erwan Bouroullec, 2024

Further functional features:

- Memory function with up to 4 memory positions.
- Automatic prompt on LED display reminding the user to change from sitting to standing at three self-defined intervals..
- OLED display showing table height setting or for error code readout.
- Bluetooth interface for Desk Control™ app. Enables a connection to the table controls, so the user can set personal goals for working in a standing position and define individual time intervals with the memory function.

For safety reasons, the Bluetooth interface does not allow control of table height adjustment by app.

Horizontal leg

Description: Horizontal leg made of die-cast aluminium, powder-coated in the same colour as leg column, equipped with glides made of injection-moulded plastic for levelling on uneven floors (range 0-10 mm).

Dimensions: W 701 x D 75 x H 53 mm.

Frame tubing

Description: frame constructed from rectangular metal tubing, powder-coated, cut-outs with safety radius for efficient cable management. Connected to top of columns as a support for the table top.

Dimensions: W 1258/W 1458/W 1658 x D 30 x H 40 mm.

Safety: all corners and edges are rounded.

Die-cast side element

Description: die-cast zinc, powder-coated finish, attached to top of column. Serves as mount for strain relief and CPU holder.

Dimensions: W 400 x D 40 x H 49 mm.

Cable cover made of polyester fleece

Description: cable cover made of polyester fleece panels in various colours. The material has effective acoustic properties.

Screwed directly to the table top and tubular frame, it conceals the frame elements as well as the height-adjustment controls, sensor and cables situated between them.

Dimensions after assembly: W 1274/W 1474/W 1674 x D 266 x H 44 mm, material thickness 3 mm.

Cable tray made of polyester fleece

Description: thermoformed polyester fleece cable tray in various colours. The material has effective acoustic properties. Easy access through zip opening and press stud flap along the back.

Dimensions after assembly for tables with depth of 70 cm: W 1274 x D 502 x H 70 mm, material thickness 3.8 mm.

Dimensions after assembly for tables with depth of 80 cm: W 1474/W 1674 x D 552 x H 70 mm, material thickness 3.8 mm.

Additional elements

Bracket

Description: two-piece bracket mount, powder-coated, with pressure plate in die-cast zinc; for table top thickness 22-28 mm. One adapter for a monitor arm or lamp can be attached per bracket mount. Can be attached anywhere along the edge of the table top, without tools, using a thumb screw. If the bracket mount is used to hold monitor arms, the thumb screw is replaced by a grub screw for added stability. If no adapter is attached, the bracket is delivered with a powder-coated metal cover over the connection point. The metal cover must be removed to allow retroactive attachment of an adapter.

Dimensions: W 105 x D 65 mm, surface covered on table top. Height measured from table surface 17 mm, table overhang 15 mm.

Lamp adapter for bracket mount

Description: for attachment to bracket mount; turned part in polished aluminium.

Version: for lamps incl. plastic sleeve with inner diameter of 10 or 11 mm.

Dimensions: H 45 mm, outer diameter 30 mm.

Tyde 2 Home Desk

Ronan & Erwan Bouroullec, 2024

vitra.

Monitor adapter for bracket mount

Description: for attachment to bracket mount; polished die-cast aluminium.

Version: incl. rotation lock, exclusively for monitor arm Humanscale M2.1.

Dimensions: H 45 mm, outer diameter 30 mm.

CPU holder

Description: for attachment under the table top, mounted on the die-cast side element. CPU holder made of powder-coated sheet steel. Fastening strap; tightens with plastic buckle. Socket under table provides CPU with access to power connections.

Can be mounted facing inwards or outwards. Max. dimensions of CPU: D 650 x H 490 mm, min. dimensions of CPU: W 45 x H 175 mm.

Dimensions of sheet steel holder: W 240 x D 100 x H 375-490 mm.

Safety: max. load capacity: 15 kg

Electrification

General note

VDE regulations specify that electrical work may only be performed by qualified technicians. Special training is not required for the routing and attachment of cables with plug connections. It is advisable to assess the number and type of devices requiring power connections before ordering electrical components. Our sales team will be happy to provide assistance.

Cable outlet

Description: cable outlet made of plastic (two-part), rotating cover.

Dimensions: Ø 80 mm, protrudes 3 mm from surface.

Power outlets

Description: holds 1 under-table power outlet. Connected to table top (facing forwards) with metal bracket. Sockets are supplied with GST18 plugs.

Cable tube

Description: flexible cable tube made of polyethylene with hook-and-loop fasteners on both ends for attachment. Reconfiguration is possible without a loss of cable length. Holds up to 4 cables.

Safety: cable strain relief is always integrated in die-cast side element.

Dimensions: L 1250 mm, L 1100 mm for clusters with cable channel.

Certificates

GS (with the exception of black table tops)

BIFMA

Greenguard Gold

CE